

7/18 Abel Street,  
 PENRITH, NSW 2750, AUSTRALIA  
 Telephone: 1800 TechDry | 1800 832 437  
 Facsimile: 02 9423 4621  
 Website: www.1800techdry.com.au  
 E-mail: info@1800techdry.com.au

## MATERIAL SAFETY DATA SHEET

DPC CREAM

Page 1 of 2

Issued: 1/11/2008

### Not classified as hazardous according to criteria of Worksafe Australia

#### Identification

Product name:	DPC CREAM
Other names:	Silane/siloxane cream
Manufacturer's code:	RPSSDPC
UN number:	Not allocated
D.G. class:	Not allocated
Subsidiary risk:	Not allocated
Hazchem code:	Not allocated
Poisons schedule no:	Not allocated
Package group:	Not allocated

#### Use

Silane/siloxane cream is used as silicone damp-course for treatment of rising damp in masonry walls including brick, stone and concrete masonry.

#### Physical properties

Appearance:	Consistent firm white cream
Boiling point:	≥100 °C
Vapour pressures (20 °C):	Not allocated
Density (20 °C):	approx. 0.90 g/ml
Flash point:	>61 °C
Flammability limits (%):	Not allocated
Solubility in water:	Miscible

#### Other properties

Autoignition point:	Not allocated
Vapour density (air=1):	Not allocated
pH:	7-8
Viscosity (20 °C):	>5,000cps (Thixotropic cream)

#### Ingredients

Chemical entity	CAS number	Proportion
Silane/siloxane mixture		>80%
Non hazardous additives		<10%
Water		<20%

#### Hazard Health Information

##### **Health Effects:**

To the best of our knowledge, the adverse health effects of this product as a whole have not been determined. However, normal industrial hygiene measures should be followed when handling chemicals.

##### **Acute:**

##### **Swallowed:**

Harmful if swallowed. It may cause irritation to mouth, throat and stomach.

##### **Eye:**

Silane/siloxanes may cause eye irritation.

##### **Skin:**

Silane/siloxanes may be irritating to the skin.

##### **Inhaled:**

It may cause irritation to the mucous membranes and respiratory tract. Over exposure can result in drowsiness, nausea, vomiting and dizziness. An aerosol mist of the silane and siloxane may cause lung damage if inhaled.

##### **Chronic:**

Not known.

**First Aid:**

**Swallowed:** If swallowed, do not induce vomiting. Give a glass of water. Never give anything by mouth to an unconscious person. Get prompt medical attention.

**Eye:** Flush eyes with copious amounts of water for at least 15 minutes. Obtain medical attention.

**Skin:** Remove contaminated clothing and wash skin thoroughly. Wash clothing before reuse. Seek medical advice if effects persist.

**Inhaled:** Remove affected victim from exposure area to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek prompt medical advice.

**First Aid Facilities:** Washing facilities are strongly recommended for handling chemicals.

**Advice to Doctor:** Treat symptomatically.

**Precautions For Use**

**Exposure Standards:** There is no data allocated with this product. Ethanol may release from the hydrolysis of the silane, the standard exposure of ethanol is: 1000ppm (TWA)

**Engineering Controls:** Keep away from sources of ignition. Take precautionary measures against static discharges. Provide sufficient ventilation. Use local exhaust ventilation if need.

**Personal Protection:** Wear chemical resistant safety glasses or goggles, gloves and protective clothing. Wear approved respiratory protection (AS1716/1715) if there is a risk of exposure to intensive vapour concentrations. Wash hands after handling.

**Flammability:** This product contains more than 80% combustible organic liquid. Avoid heat and all ignition sources. Use only in well ventilated areas.

**Safe Handling Information**

**Storage and Transport:** Consult AS1940 and relevant state or territory regulations on safe storage and handling. Store at temperature between 0 °C to 30°C in a cool and well-ventilated area away from any heat and ignition sources.

**Spills and disposal:** Wear full protective clothing while attending to spills. Extinguish all ignition sources. Prevent entry into drainage systems, sewers and waterways. Collect with inert absorbent material such as sand or earth. Ensure waste disposal conforms to local waste disposal regulations.

**Fire/Explosion Hazard:** Shut and remove ignition sources if safe to do so. Use dry powder, sand, and foam and/or carbon dioxide extinguisher. Wear a breathing apparatus and full protective measures while attending to the hazard. Prevent the product from entering drains or waterways. Hazard decomposition products may include carbon oxides, silicone dioxide and traces of formaldehyde.

**Other Information**

**Toxicity data:** Not known

**Contact Point** For further information please contact Tech-Dry tel: 61 3 9699 8202 (all hours).

**Important Note**

To the best of our knowledge, the information sources for the preparation of this document were correct and complete at the time of writing. The information is therefore subject to possible change from time to time and cannot be guaranteed. This document should be taken as a safety guide for the product and its recommended uses but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product or any material existing within the product. For further information, please contact Tech-Dry Building Protection Systems Pty. Ltd.